

50 TONNE TRIPLE RAM AIR HYDRAULIC TROLLEY JACK - AH50-3

50 TONNE TRIPLE RAM AIR HYDRAULIC TROLLEY JACK FOR LOW BUSES AND OTHER LOW CLEARANCE VEHICLES

Item number: 093f65e080a2



DESCRIPTION

50/25/10 Tonne Triple Ram Air/Hydraulic Trolley Jack

- Minimum height of only 150mm, combined with a high lifting capacity
- Telescopic cylinders ensure an excellent maximum lift with a low closed height
- Designed for heavy-duty, intensive commercial use.
- Hard chromium plated piston rod for long life.
- Built-in safety overload valve.
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering.
- Ergonomic Handle with push buttons.
- Supplied with 2 extensions as standard (50/100mm)

SPECIFICATIONS

Minimum Height (mm):	150
Weight (kg):	67
Frame Length (mm):	810
Handle Length (mm):	1160
Width (mm):	200
Capacity (kg) First Stage:	50,000
Capacity (kg) Second Stage:	25,000
Capacity (kg) Third Stage:	10,000
Max Height (mm) First Stage:	210
Max Height (mm) Second Stage:	265
Max Height (mm) Third Stage:	335
Width with Wheels (mm):	310
Air Supply:	8 - 10 Bar
Air Consumption (l/min):	350
Type:	AH50-3

ACCESSORIES: 093F65E080A2

145mm Dished Saddle
suitable for lifting over drain
plugs and differential gears

Item number: 37a749d808e4



250mm Extension Piece

Item number: fc490ca45c00



**V Saddle for lifting under
various axles**

Item number: b3e3e393c77e

