

50 TONNE TRIPLE RAM AIR/HYDRAULIC TROLLEY JACK - AH50-3H

50 TONNE TRIPLE RAM HIGH LIFT AIR HYDRAULIC TROLLEY JACK WITH A STANDARD HANDLE

Item number: 072b030ba126



DESCRIPTION

50/25/10 Tonne Triple Ram Air/Hydraulic Trolley Jack

- Minimum height of 220mm, and high lift of 560mm
- Designed for heavy-duty, intensive commercial use
- Telescopic cylinders ensure a high capacity combined with a low minimum height
- Hard chromium plated piston rod for long life
- Built-in safety overload valve
- Hand-operated dead-man's control for optimum safety whilst lifting and lowering
- Ergonomic Handle with push buttons
- For safety reasons extensions are not included with this model

SPECIFICATIONS

Minimum Height (mm):	220
Weight (kg):	73
Frame Length (mm):	810
Handle Length (mm):	1160
Width (mm):	200
Capacity (kg) First Stage:	50,000
Capacity (kg) Second Stage:	25,000
Capacity (kg) Third Stage:	10,000
Max Height (mm) First Stage:	340
Max Height (mm) Second Stage:	450
Max Height (mm) Third Stage:	560
Width with Wheels (mm):	310
Air Supply:	8 - 10 Bar
Air Consumption (l/min):	350
Type:	AH50-3H

ACCESSORIES: 072B030BA126

V Saddle for lifting under various axles

Item number: b3e3e393c77e

