

2 TONNE AIR OPERATED JACKING BEAM - SD20PHL-A

2 TONNES CLASS 4 AIR OPERATED JACKING BEAM WITH AUTOMATIC ARMS

Item number: e00da03b685a



DESCRIPTION

2 Tonnes Automatic Air Hydraulic Jacking Beam for Inspections Centres and Workshops with many Lifting Operations

- Individual joysticks control of lifting arms to avoid time consuming working operations.
- Remote control activates lowering and retraction of lifting arms to closed position.
- Placing the remote control next to the lift control panel ensures safe operation and prevents unnecessary steps.
- Unique height adjustable support arm system - designed to fit all current lifts and pits (on completion of lift specification form).
- Supplied with 3 extension sets (10/40/85mm) and rubber cushion.

*Not suitable for Class 4 MOT application

SPECIFICATIONS

Capacity (kg):	2,000
Minimum Height (mm):	200
Air Consumption (l/min):	400 - 700
Stroke (mm):	250
Telescopic Arm (mm):	780 - 1500
Width [Without Support Arms] (mm):	780 - 1180
Lifting Frame Height (mm):	120
Lifting Frame Depth (mm):	250
Air Supply (Bar):	8 - 10
Weight No Support Arms (kg):	120
Type:	SD20PHL-A

ACCESSORIES: E00DA03B685A

130mm Metal Extension Piece for SD Jacking Beams

Item number: 0a09c8844ba8



Adjustable saddle with spindle which increases the lifting height by 106-240mm for SD Jacking Beams

Item number: 8d5e957f2978



Rubber Saddle For 10mm Extension

Item number: a8f15eda80c5

