

2 TONNE AIR OPERATED JACKING BEAM - SD20PHL

2 TONNES CLASS 4 AIR OPERATED JACKING BEAM

Item number: 3988c7f88ebc



DESCRIPTION

2 Tonnes Air Hydraulic Jacking Beam for Passenger Cars and Vans

- Quick and efficient lifting due to reliable pump.
- Low closed height of only 180mm makes it ideal for vehicles with a low clearance.
- Flexible top support beam can be extended up to 1610mm.
- Unique height adjustable support arm system - designed to fit all current lifts and pits (on completion of lift specification form).
- Two-handed lowering operation with dead man's release, automatic safety locking device and overload valve for optimum safety.
- Supplied with 3 extension sets (10/40/85mm) and rubber cushion for protection of car body.
- (Not suitable for Class IV MOT application)

SPECIFICATIONS

Capacity (kg):	2,000
Minimum Height (mm):	180
Air Consumption (l/min):	400 - 700
Stroke (mm):	250
Telescopic Arm (mm):	780 - 1610
Width [Without Support Arms] (mm):	780 - 1180
Lifting Frame Height (mm):	120
Lifting Frame Depth (mm):	250
Air Supply (Bar):	8 - 10
Weight No Support Arms (kg):	110
Type:	SD20PHL

ACCESSORIES: 3988C7F88EBC

130mm Metal Extension Piece for SD Jacking Beams

Item number: 0a09c8844ba8



Adjustable saddle with spindle which increases the lifting height by 106-240mm for SD Jacking Beams

Item number: 8d5e957f2978



Adjustable Saddle which increases the lifting height by 32-92mm for SD Jacking Beams

Item number: 47d1e990583c



Airline Connection Set for jacking beam

Item number: 903ce9225fca



**For the FSD6 which increases
the lifting height by 60mm**

Item number: f2217062e9a3



**Rubber cushion to be used
with the S-Saddle for
protection of car body**

Item number: 43ec517d68b6



**Saddle Cushion to fit WDK
Range up to 2 Tonne and
other applications**

Item number: 7ef605fc8dba

