

2.6 TONNE AIR OPERATED CLASS 7 JACKING BEAM - SD26PHL-A

2.6 TONNES AIR OPERATED CLASS 7 JACKING BEAM WITH AUTOMATIC ARMS

Item number: 1385974ed590



DESCRIPTION

2.6 Tonnes Automatic Air Hydraulic Jacking Beam for Inspections Centres and Workshops with many Lifting Operations

- Individual joysticks control of lifting arms to avoid time consuming working operations.
- Remote control activates lowering and retraction of lifting arms to closed position.
- Placing the remote control next to the lift control panel ensures safe operation and prevents unnecessary steps.
- Unique height adjustable support arm system - designed to fit all current lifts and pits (on completion of lift specification form).
- Supplied with 3 extension sets (10/40/85mm) and rubber cushion.

* Not suitable for Class 7 applications

SPECIFICATIONS

Capacity (kg):	2,600
Minimum Height (mm):	200
Air Consumption (l/min):	400 - 700
Stroke (mm):	250
Telescopic Arm (mm):	780 - 1500
Width [Without Support Arms] (mm):	780 - 1180
Lifting Frame Height (mm):	120
Lifting Frame Depth (mm):	250
Air Supply (Bar):	8 - 10
Weight No Support Arms (kg):	120
Type:	SD26PHL-A

ACCESSORIES: 1385974ED590

130mm Metal Extension Piece for SD Jacking Beams

Item number: 0a09c8844ba8



40mm High Rubber Support Block for the protection of the car body.

Item number: 2b24d495052a



80mm High Rubber Support Block for protection of the the car body.

Item number: a5e00132373a



Adjustable saddle with spindle which increases the lifting height by 106-240mm for SD Jacking Beams

Item number: 8d5e957f2978



**Airline Connection Set for
jacking beam**

Item number: 903ce9225fca



**Rubber Saddle For 10mm
Extension**

Item number: a8f15eda80c5

