

2.6 TONNES AIR OPERATED CLASS 7 JACKING BEAM - SD26PHL

2.6 TONNES AIR OPERATED CLASS 7 JACKING BEAM

Item number: 013d407166ec



DESCRIPTION

2.6 Tonnes Air Hydraulic Jacking Beam for Passenger Cars and Vans

- Quick and efficient lifting due to reliable pump.
- Low closed height of only 180mm makes it ideal for vehicles with a low clearance.
- Flexible top support beam can be extended up to 1610mm.
- Unique height adjustable support arm system - designed to fit all current lifts and pits (on completion of lift specification form).
- Two-handed lowering operation with dead man's release, automatic safety locking device and overload valve for optimum safety.
- Supplied with 3 extension sets (10/40/8mm) and rubber cushion for protection of car body.
- (Not suitable for Class 7 MOT applications)

SPECIFICATIONS

Capacity (kg):	2,600
Minimum Height (mm):	180
Air Consumption (l/min):	400 - 700
Stroke (mm):	250
Telescopic Arm (mm):	780 - 1610
Width [Without Support Arms] (mm):	780 - 1180
Lifting Frame Height (mm):	120
Lifting Frame Depth (mm):	250
Air Supply (Bar):	8 - 10
Weight No Support Arms (kg):	110
Type:	SD26PHL

ACCESSORIES: 013D407166EC

40mm High Rubber Support Block for the protection of the car body.

Item number: 2b24d495052a



80mm High Rubber Support Block for protection of the the car body.

Item number: a5e00132373a



Adjustable saddle with spindle which increases the lifting height by 106-240mm for SD Jacking Beams

Item number: 8d5e957f2978



Adjustable Saddle which increases the lifting height by 32-92mm for SD Jacking Beams

Item number: 47d1e990583c



**Airline Connection Set for
jacking beam**

Item number: 903ce9225fca



**For the FSD6 which increases
the lifting height by 60mm**

Item number: f2217062e9a3



**Rubber cushion to be used
with the S-Saddle for
protection of car body**

Item number: 43ec517d68b6



**Rubber Saddle For 10mm
Extension**

Item number: a8f15eda80c5

