

20 TONNES AIR HYDRAULIC TWIN RAM HEAVY DUTY JACKING BEAM - FL200-2

20 TONNES AIR HYDRAULIC TWIN RAM HEAVY DUTY JACKING BEAM

Item number: bd4c9ab730f5



DESCRIPTION

20 Tonnes Air Hydraulic Twin Ram Jacking Beam

- 2 individually controlled rams offer safe and balanced lifting.
- Transversely sliding rams.
- Rapid and precise air hydraulic unit with high speed ram travel.
- Simple modern design with control panel at ergonomical working height.
- Can be made to fit all lifts due to its adjustable frame.
- Dead man's release and safety overload valve for optimal safety.
- Supplied with 2 x 100mm extensions.
- When ordering fill out spec. form.

SPECIFICATIONS

Capacity (kg):	20,000
Minimum Height (mm):	380
Max Height (mm):	580
Weight (kg):	202
Width (mm):	590 - 1410
Air Consumption (l/min):	350
Stroke (mm):	200
Air Supply (Bar):	08 - 12 bar
Depth (mm):	665
Lifting Points (mm):	200 - 1160
Additional Info:	Distance between lifting points: 200-640 mm / 200-990 mm / 200-1160 mm
Type:	FL200-2

ACCESSORIES: BD4C9AB730F5

Trolley for installation of heavy duty jacking beams on lifts

Item number: 58a2fc6ed39f

